FAA BULK LEAD ANALYSIS (24 Hour Turn Around)

CALL NUMBER: LS95

SAMPLE: 121008.417.01-L 121008.417.02-L 121008.417.03-L	LOCATION: Exterior Interior Exterior	MATERIAL: Beige paint on stucco wall Beige paint on drywall wall Beige paint on wood winder	lls
Sampler's Signature:	Beth	<u>.</u>	
Total Analysis (FAA) Total Asbestos Analy Total Lead Analysis C Total Analysis Cost: \$	Price Quote: \$16.00/2 sis Cost: \$12.00 x 31. \$ Cost: \$16.00 x 3 Sampl \$372.00 + \$48.00 = \$42	Samples = \$372.00 e = \$48.00	
Relinquished By: Received By: Relinquished By: Received By:	Holones	Date: 1/14/2009 Date:	Time: 10:30 Time: 10:30 Time: 10:30



Forensic Analytical

Bulk Asbestos Analysis

(EPA Method 600/R-93-116, Visual Area Estimation)

LAAFB - 61 CELS/CELEV Beth Jones 438 N. Aviation Suite B272, 3rd Floor El Segundo, CA 90245-4659

 Client ID:
 6896

 Report Number:
 B120531

 Date Received:
 01/15/09

 Date Analyzed:
 01/16/09

 Date Printed:
 01/16/09

 First Reported:
 01/16/09

Job ID/Site: AS94

FASI Job ID: 6896

Date(s) Collected: 01/14/2009

Total Samples Submitted: 32
Total Samples Analyzed: 25

Sample ID	Lab Number	Asbestos Type	Percent in Layer	Asbestos Type	Percent in Layer	Asbestos Type	Percent in Layer
121008.417.01 Layer: White Non-Fibrous Material Layer: Yellow Mastic	10832611		ND ND				
Total Composite Values of Fibrous Com Cellulose (Trace)	ponents: A	sbestos (ND)					
121008.417.02 Layer: Off-White Cementitious Material Layer: Green Cementitious Material Layer: Paint	10832612	Chrysotile	Trace ND ND	See att	ached ng ref	point sults (0.08%CH

Total Composite Values of Fibrous Components:

Asbestos (Trace)

Cellulose (Trace)

121008.417.03

Comment: Sample not analyzed due to prior positive result in series.

-121008.417.04

10832614

10832613

Comment: Sample not analyzed due to prior positive result in series.

121008.417.05

121008.417.06

10832615

Layer: White Drywall ND

Total Composite Values of Fibrous Components:

Asbestos (ND)

Cellulose (20 %)

10832616

Layer: White Drywall

ND

Layer: Paint

ND

Total Composite Values of Fibrous Components:

Asbestos (ND)

Cellulose (20 %)

121008.417.07

10832617

Layer: White Drywall

Layer: Off-White Skimcoat/Joint Compound

ND ND

Layer: Paint

ND

Total Composite Values of Fibrous Components:

Asbestos (ND)

Cellulose (20 %)


Report Number: B120531

Date Printed:

01/16/09

Sample ID	Lab Number	Asbestos Type	Percent in Layer	Asbestos Type	Percent in Layer	Asbestos Type	Percent in Layer
121008.417.08	10832618						
Layer: Light Grey Sheet Flooring			ND				
Layer: Fibrous Backing			ND				
Layer: Yellow Mastic			ND				
Total Composite Values of Fibrous Com Cellulose (20 %) Fibrous Glass (5 %		sbestos (ND)					
121008.417.09	10832619	(
Layer: Light Grey Sheet Flooring	10052015		ND				
Layer: Fibrous Backing			ND				
Layer: Yellow Mastic			ND				
Total Composite Values of Fibrous Com	nonënts: A	sbestos (ND)					
Cellulose (20 %) Fibrous Glass (5 %		•					
, ,	10832620	2 (10 70)					
121008.417.10 Layer: Light Grey Sheet Flooring	10032020		ND				nomenta to d
Layer: Fibrous Backing			ND				1 31 In
Layer: Yellow Mastic			ND				3 1
Total Composite Values of Fibrous Com	nonante: A	sbestos (ND)					
Cellulose (20 %) Fibrous Glass (5 %	_	• .					,
011409.33.01	10832621						
Layer: Grey Sheet Flooring			ND				
Total Composite Values of Fibrous Com Cellulose (Trace)	ponents: A	sbestos (ND)					
011409,33.02	10832622						
Layer: Grey Sheet Flooring			ND				
Total Composite Values of Fibrous Com Cellulose (Trace)	ponents: A	sbestos (ND)					
011409.33.03	10832623						
Layer: Grey Sheet Flooring			ND				
Total Composite Values of Fibrous Com	nonents: A:	sbestos (ND)					4.00
Cellulose (Trace)		- in					4.1
- 011409.33.04	10832624						e garante de
. Layer: Grey Sheet Flooring	10032024		ND				
Layer: Fibrous Backing			ND				
Layer: Yellow Mastic			ND				
Total Composite Values of Fibrous Comp	oonents: As	sbestos (ND)					
Cellulose (20 %) Fibrous Glass (5 %) Synthetic	, ,					
011409.33.05	10832625						
Layer: Grey Cementitious Material			ND		y-		
Layer: Black Tar			ND				
Total Composite Values of Fibrous Comp Cellulose (Trace)	oonents: As	sbestos (ND)					
~ · · · · · · · · · · · · · · · · · · ·							

Client Name: LAAFB - 61 CELS/CELEV



Bulk Asbestos Material Analysis

(EPA Method 600/R-93/116, Point Count Analysis)

LAAFB - 61 CELS/CELEV Beth Jones 438 N. Aviation Suite B272, 3rd Floor El Segundo, CA 90245-4659

Job ID/Site: AS94

Client ID: Report Number: Date Received: 6896 N001247 01/15/09

Date Analyzed:
Date Printed:

01/23/09 01/23/09

FASI Job ID:

6896

Sample Preparation and Analysis:

Each sample was prepared using the gravimetric technique. A representative subsample was weighed, ashed for eight hours, and reweighed determine the proportion of the organic component. The ashed residue was ground in concentrated hydrochloric acid, dried and reweighed to determine the acid-soluble component weight percentage. The residual material was analyzed for asbestos using polarized light microscopy. Asbestos quantitation was performed using the semi-quantitative Point Count method following the general guidelines in EPA Method 600/R-93/116. The analytical sensitivity for the method is calculated as the asbestos concentration that results from one point counted in the analysis adjusted using the residual weight of the sample. The limit of detection for this method has not been determined.

S	Sample ID	Lab Number	Sample Description		
1	21008.417.02	10832612	Off-White Cementitious Material		
	Point Count Results:			Gravimetry Results:	
	Number of asbestos points cour	nted:	1	Organic weight percentage:	2.76
	Number of non-empty points:	100	00	Acid-soluble weight percentage	16.36
	Percent asbestos in layer:	0.0	08	Residual weight percentage:	80.88
	Analytical sensitivity (%):	0.0	08		
•	Asbestos type(s) detected:	Chrysotile			

Comment:

ll ne

Vindho

James Flores, Laboratory Supervisor, Hayward Laboratory

Analytical results and reports are generated by Forensic Analytical at the request of and for the exclusive use of the person or entity (client) named on such report. Results, reports or copies of same will not be released by Forensic Analytical to any third party without prior written request from client. This report applies only to the sample(s) tested. Supporting laboratory documentation is available upon request. This report must not be reproduced except in full, unless approved by Forensic Analytical. The elign is solely responsible for the use and interpretation of test results and reports requested from Forensic Analytical. This report must not be used by the client to claim product endorsement by NVLAP or any other agency of the U.S. Government. Forensic Analytical is not able to assess the degree of hazard resulting from materials analyzed. Forensic Analytical reserves the right to dispose of all samples after a period of thirty (30) days, according to all state and federal guidelines, unless otherwise specified. All samples were received in acceptable condition unless otherwise noted.





Forensic Analytical

Job ID / Site: LS95 - BPA# F04693-03-A-0005

Metals Analysis of Paints

LAAFB - 61 CELS/CELEV Beth Jones 438 N. Aviation Suite B272, 3rd Floor El Segundo, CA 90245-4659 Client ID: 6896 Report Number: M100276 Date Received: 01/15/09 Date Analyzed: 01/16/09 Date Printed: 01/16/09

First Reported:

01/16/09

FASI Job ID:

6896

Sample Number	Lab Number	Analyte	Result	Result Units	Reporting Limit*	Method Reference
121008.417.01-L	30338929	Pb	0.013	wt%	0.007	EPA 3050B/7420
121008.417.02-L	30338930	Pb	0.010	wt%	0.006	EPA 3050B/7420
121008.417.03-L	30338931	Pb	4.0	wt%	0.2	EPA 3050B/7420

Dave Sandusky, Laboratory Supervisor, Hayward Laboratory

Analytical results and reports are generated by Forensic Analytical at the request of and for the exclusive use of the person or entity (client) named on such report. Results, reports or copies of same will not be released by Forensic Analytical to any third party without prior written request from client. This report applies only to the sample(s) tested. Supporting laboratory documentation is available upon request. This report must not be reproduced except in full, unless approved by Forensic Analytical. The client is solely responsible for the use and interpretation of test results and reports requested from Forensic Analytical. Forensic Analytical is not able to assess the degree of hazard resulting from materials analyzed. Forensic Analytical reserves the right to dispose of all samples after a period of thirty (30) days, according to all state and federal guidelines, unless otherwise specified. Any modifications that have been made to referenced test methods are documented in Forensic Analytical's Standard Operating Procedures Manual. Sample results have not been blank corrected. Quality control and sample receipt condition were acceptable unless otherwise noted.

^{*} The Reporting Limit represents the lowest amount of analyte that the laboratory can confidently detect in the sample, and is not a regulatory level. The Units for the Reporting Limit are the same as the Units for the Final Results.

ASBESTOS/LEAD SURVEY REQUEST FORM

SURVEY #: 96/97

REQUESTER'S NAME AND PHONE #: Carol Glover

LOCATION: Fort MacArthur, Animal Clinic, Building 417

DATE SUBMITTED: 3/3/2009

W.O./J.O. #:

DATE REQUIRED (At least 10 days from submission): ASAP

DESCRIPTION OF PROPOSED WORK: Demolish Building

LIST SPECIFIC AREAS THAT MAY BE DISTURBED: All building components.

ARE SITE MAPS, SKETCHES, and SOW AVAILABLE? NO

XYES, Please attach all building sketches and drawings

& place in CEZV mailbox)

CUSTOMER CONTACT INFORMATION (Name and Phone #):

DO NOT WRITE BELOW THIS LINE FOR CELS/CEAE USE

PREVIOUS SAMPLES COLLECTED IN HOMOGENEOUS (Similar) AREAS? YES, SEE BELOW NO

INSPECTION DATE: 02/09/2009

INSPECTION ATTENDEES: Beth Jones

INSPECTION INFORMATION: Conducted inspection and sampling of kitchen area

SAMPLE DATA: ASBESTOS

Sample ID:	Location: (see attached)	Material:	Results: Asbestos (%)
121008.417.01	Interior	White leveling compound beneath floor sheeting	ND
121008.417.02	Exterior	Stucco Siding	0.08% Chrysotile
121008.417.03			
121008.417.04			
121008.417.05	Interior	Drywall walls and associated joint compounds	ND – all layers
121008.417.06			
121008.417.07			
121008.417.08	Interior	Light Gray floor sheeting and associated backing	ND – all layers
121008.417.09		and mastics	
121008.417.10			
121008.417_AAA	Exterior - roof	Built up roofing system (felts, mastics and	Assumed Asbestos
		shingles)	

ND denoted Non-Detect for asbestos fiber. Sample 121008.417.02 was determined to contain 0.08% Chrysotile asbestos after 1,000 point count analysis. Any material containing greater than 0.01% asbestos is considered and asbsetos containing material (ACM) in the State of California.

ASBESTOS/LEAD SURVEY REQUEST FORM

SAMPLE DATA: LEAD

Sample ID:	Location:	Material:	Results: Lead (ppm)
121008.417.01-L	Exterior	Beige paint on stucco siding	130
121008.417.02-L	Interior	Beige paint on drywall walls	100
121008.417.03-L		Beige paint on exterior and interior wood window components	40,000

Any material containing greater than 600 parts per million (ppm) is considered lead-based in the State of California.

RISK ASSESSMENT REQUIRED: YES NO

FINDINGS AND RECOMMENDATIONS:

ASBESTOS

- Asbestos was identified in the exterior stucco siding and built up roofing system. (see survey results above).
- These results are for estimation purposes only. The Contractor is responsible for verifying all data as required.
- If any suspect materials not identified above are identified during the project, work must stop until sampling can be conducted, the contractor will be responsible for conducting all required abatement activities as required per Federal, State and Local regulations.
- If asbestos-containing building materials are disturbed at any time during the project, or if removal is required to complete the project, a certified/registered asbestos abatement contractor shall be utilized to properly remove or impact asbestos-containing materials and dispose of asbestos waste properly.
- All work must comply with Environmental Engineering Asbestos Abatement and Disposal Requirements Specifications 02085.

LEAD-BASED PAINT

- Lead-based coatings were identified in the white paint associated with interior and exterior wood window components (see survey results above).
- If lead-based coatings are to be disturbed at any time during the project, or if removal is required to complete the project, a certified/registered lead abatement contractor shall be utilized to properly remove or impact lead containing materials and dispose of lead waste properly.
- All work must comply with Environmental Engineering Lead-based Paint Abatement and Disposal Requirements Specifications 02086

Should you have any questions, please contact Beth Jones at (310) 653-5496

INSPECTOR: Beth Jones DATE: 3/3/2009